Paper / Subject Code: 32002 / Electrical Machines - III

1T00825 - T.E.(ELECTRICAL)(Sem V) (Choice Based) / 32002 - Electrical Machines-III

(Tille, SHOUIS) MAX MAXIS	(Time: 3Hours)	MAX MARKS	80
---------------------------	----------------	-----------	----

NOTE

1.Question	number	1	is	compu	lsory

- 2. Attempt any three from the remaining
- 3. Figures to right indicates full marks
- 4. Assume suitable data if necessary and mention the same

1.		Attempt any four of the following:	20
	a)	What is the objective of performing no load and blocked rotor test on 3 phase induction motor?	05
	b)	Explain capacitor start 1-phase single phase Induction motor.	05
	c)	Explain dispersion coefficient.	05
	d)	What is the significance of magnetic loading?	05
	e)	Why do we need to apply reduced voltage at the time of starting of 3- phase Induction motor?	05
2.		\$\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	20
	a)	Explain the effect of frequency and voltage variation on Induction Motor performance.	10
	b)	A 3 phase, 6 poles, star connected, Induction motor connected to 415V, 50 Hz supply has the rotor resistance and standstill reactance are 0.12 and 0.85 ohms per phase. The stator to rotor turns ratio is 1.8 and full load slip is 4%. Calculate the full load torque, maximum torque and the speed at maximum torque.	10
3.			20
	a)	Derive the output equation of a 3-phase Induction motor in terms of main dimensions.	10
	b)	Discuss the concept of Carter's coefficient in detail	10
4.	200		20
80	a)	What is frame and frame size in case of Induction motor? Draw a figure showing structural dimensions of standard frame?	10
	b)	Determine the main dimension, turns per phase, no. of slots, conductor cross section and area of slot for a 3-phase, 50Hz, 4 pole, 250HP, 400V,1410rpm, delta connected squirrel cage induction motor with the data given: average flux density in air gap = 0.5 Wb/m², ampere conductor per meter = $30,000$ A/m, efficiency = 90% , pf = 0.9 , winding factor = 0.955 , current density = 3.5 A/mm², slot space factor = 0.4 , ratio of length of core to pole pitch = 1.2 .Assume 5 slots per pole per phase. Assume three phase fault	10
	Y 100 11 100 1	Y AT J. NOT AT LACTA TO 1967 J. TO 1. NOT	

55803 Page **1** of **2**

Paper / Subject Code: 32002 / Electrical Machines - III

b) A 15kW,440V , 4pole 50Hz, 3–Φ, star connected induction m following test results :					action motor g
			Line Voltage	Line current	Power input
		No load Test	440V	10A	1310W
		Blocked rotor test	200V	50A	7100W

6.	Write short notes on (any two)	20
a)	Double field revolving theory	10
b)	Cogging and crawling in $3 - \Phi$ induction motor.	10
c)	Reluctance starting in 1- phase Induction motor.	10

55803 Page **2** of **2**